

# THERMA-TRU CORPORATION ACOUSTICAL PERFORMANCE TEST REPORT

## SCOPE OF WORK

ASTM E90 SOUND TRANSMISSION LOSS TESTING ON A  
3080 FLUSH DOOR WITH MINIBLINDS, SIDE-HINGED SINGLE DOOR SYSTEM

## REPORT NUMBER

K7954.01-113-11-R2

## TEST DATE

03/17/20

## ISSUE DATE

03/19/20

## REVISION 2 DATE

04/12/22


## PAGES

22

## DOCUMENT CONTROL NUMBER

RT-R-AMER-Test-2756 (01/24/19)

© 2017 INTERTEK



## TEST REPORT FOR THERMA-TRU CORPORATION

Report No.: K7954.01-113-11-R2

Revision 2 Date: 04/12/22 Date: 03/19/20

### REPORT ISSUED TO

#### THERMA-TRU CORPORATION

6214 Monclova Road  
Maumee, Ohio 43537

### SECTION 1

#### SCOPE

Intertek Building & Construction (B&C) was contracted by Therma-Tru Corporation to conduct a sound transmission loss test. Results obtained are tested values and were secured by using the designated test methods. The complete test data is included herein. The client provided the test specimen. All measurements were conducted in the HT test chambers at Intertek B&C located in York, Pennsylvania.

This report does not constitute certification of this product nor an opinion or endorsement by this laboratory. Intertek B&C will service this report for the entire test record retention period. The test record retention period ends four years after the test date. Test records, such as detailed drawings, datasheets, representative samples of test specimens, or other pertinent project documentation, will be retained for the entire test record retention period.

For INTERTEK B&C:

<b>COMPLETED BY:</b>	Andrew M. Johnston	<b>REVIEWED BY:</b>	Kurt A. Golden
	Technician		Senior Project Lead
<b>TITLE:</b>	Acoustical Testing	<b>TITLE:</b>	Acoustical Testing
<b>SIGNATURE:</b>		<b>SIGNATURE:</b>	
<b>DATE:</b>	04/12/22	<b>DATE:</b>	04/12/22

AMJ:jmcs

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample(s) tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.



**TEST REPORT FOR THERMA-TRU CORPORATION**

Report No.: K7954.01-113-11-R2

Revision 2 Date: 04/12/22 Date: 03/19/20

**SECTION 2**

**SUMMARY OF TEST RESULTS**

<b>SERIES/MODEL</b>	3080 Flush glazed door with miniblinds
<b>TYPE</b>	Side-hinged single door system
<b>DESCRIPTION</b>	1" IG (1/8" tempered, 3/4" air space, 1/8" tempered), bottom door

**TEST OPTION K7954.01A (BOTTOM DOOR)**

<b>TEST CONDITION</b>	Operable with blinds up
<b>DATA FILE NO.</b>	K7954.01A3
<b>STC</b>	30
<b>OITC</b>	26

<b>TEST CONDITION</b>	Operable with blinds down and closed
<b>DATA FILE NO.</b>	K7954.01A4
<b>STC</b>	30
<b>OITC</b>	25

**TEST OPTION K7954.01B (MIDDLE DOOR)**

<b>TEST CONDITION</b>	Operable with blinds up
<b>DATA FILE NO.</b>	K7954.01B
<b>STC</b>	30
<b>OITC</b>	25

<b>TEST CONDITION</b>	Operable with blinds closed
<b>DATA FILE NO.</b>	K7954.01B1
<b>STC</b>	30
<b>OITC</b>	25

**TEST OPTION K7954.01C (TOP DOOR)**

<b>TEST CONDITION</b>	Operable with blinds up
<b>DATA FILE NO.</b>	K7954.01C
<b>STC</b>	30
<b>OITC</b>	25

<b>TEST CONDITION</b>	Operable with blinds down and closed
<b>DATA FILE NO.</b>	K7954.01C1
<b>STC</b>	30
<b>OITC</b>	25

## TEST REPORT FOR THERMA-TRU CORPORATION

Report No.: K7954.01-113-11-R2

Revision 2 Date: 04/12/22 Date: 03/19/20

### SECTION 3

#### TEST METHODS

The specimens were evaluated in accordance with the following:

**ASTM E90-09 (2016)**, *Standard Test Method for Laboratory Measurement of Airborne Sound Transmission Loss of Building Partitions and Elements*

**ASTM E413-16**, *Classification for Rating Sound Insulation*

**ASTM E1332-16**, *Standard Classification for Rating Outdoor-Indoor Sound Attenuation*

**ASTM E2235-04 (2012)**, *Standard Test Method for Determination of Decay Rates for Use in Sound Insulation Test Methods*

### SECTION 4

#### SPECIMEN INSTALLATION

A sound transmission loss test was initially performed on a filler wall.

The specimen plug was removed from the filler wall assembly. The specimen was placed on an isolation pad in the test opening. Duct seal was used to seal the perimeter of the specimen to the test opening on both sides. The interior side of the specimen, when installed, was approximately 1/4" from being flush with the receive room side of the filler wall. A stethoscope was used to check for any abnormal air leaks around the test specimen prior to testing. Operable portions of the test specimen, if any, were cycled at least five times prior to testing.

#### COMMENTS

Whether the tested door system utilizes wood or composite stile edges, the ratings would remain unchanged.

## TEST REPORT FOR THERMA-TRU CORPORATION

Report No.: K7954.01-113-11-R2

Revision 2 Date: 04/12/22 Date: 03/19/20

### SECTION 5 EQUIPMENT

The equipment listed below meets the requirements of the test methods stated in Section 3 of this report.

INSTRUMENT	MANUFACTURER	MODEL	DESCRIPTION	ASSET #	CAL DATE
Data Acquisition Card	National Instruments	PXI-4462	Data Acquisition Card	65125*	05/18
Data Acquisition Card	National Instruments	PXI-4462	Data Acquisition Card	65126*	05/18
Data Acquisition Card	National Instruments	PXI-4462	Data Acquisition Card	63763-3*	04/18
Source Room Microphone	PCB Piezotronics	378B20	Microphone and Preamplifier	64902	10/19
Source Room Microphone	PCB Piezotronics	378C20	Microphone and Preamplifier	65969	04/19
Source Room Microphone	PCB Piezotronics	378C20	Microphone and Preamplifier	INT01089	01/20
Source Room Microphone	PCB Piezotronics	378C20	Microphone and Preamplifier	65968	01/20
Source Room Microphone	PCB piezotronics	378C20	Microphone and Preamplifier	65586	01/20
Receive Room Microphone	PBC Piezotronics	378B20	Microphone and Preamplifier	64907	01/20
Receive Room Microphone	PCB Piezotronics	378B20	Microphone and Preamplifier	64908	01/20
Receive Room Microphone	PCB Piezotronics	378B20	Microphone and Preamplifier	64909	01/20
Receive Room Microphone	PCB Piezotronics	378B20	Microphone and Preamplifier	64910	01/20
Receive Room Microphone	PCB Piezotronics	378B20	Microphone and Preamplifier	64911	10/19
Receive Room Environmental Indicator	Comet	T7510	Receive Room	64915	01/20
Source Room Environmental Indicator	Comet	T7510	Source Room	64914	02/20
Microphone Calibrator	Norsonic	1251	Acoustical Calibrator	Y002919	04/19

\*- Note: The calibration frequency for this equipment is every two years per the manufacturer's recommendation.

### TEST CHAMBER

	VOLUME	DESCRIPTION
RECEIVE ROOM	234 m <sup>3</sup>	Rotating vane and stationary diffusers Temperature and humidity controlled Isolation pads under the floor
SOURCE ROOM	207 m <sup>3</sup>	Stationary diffusers only Temperature and humidity controlled

	MAXIMUM SIZE	DESCRIPTION
TL TEST OPENING	4.27 m wide by 3.05 m high	Vibration break between source and receive rooms

## TEST REPORT FOR THERMA-TRU CORPORATION

Report No.: K7954.01-113-11-R2

Revision 2 Date: 04/12/22 Date: 03/19/20

### SECTION 6

#### LIST OF OFFICIAL OBSERVERS

NAME	COMPANY
Andrew M. Johnston	Intertek B&C
Kurt A. Golden	Intertek B&C

### SECTION 7

#### TEST PROCEDURE

The sensitivity of the microphones was checked before measurements were conducted.

The transmission loss values were obtained for a single direction of measurement.

Two background noise sound pressure level and five sound absorption measurements were conducted at each of five microphone positions.

Two sound pressure level measurements were made simultaneously in receive and source rooms at each of five microphone positions.

The air temperature and relative humidity conditions were monitored and recorded during all measurements.

Data for flanking limit tests, repeatability measurements, and reference specimen tests are available upon request.

The specimen was returned per the client's request.

### SECTION 8

#### ACOUSTICAL TEST CALCULATIONS

Transmission loss (TL) at each 1/3 octave frequency is the average source room sound pressure level minus the average receive room sound pressure level, plus, 10 times the log of the specimen area divided by the sound absorption of the receive room with the sample in place.

#### STC Rating

To obtain the Sound Transmission Class (STC), read the TL of the contour curve at 500 Hz. The sum of the deficiencies below the contour curve must not exceed 32. The maximum deficiency at any one frequency must not exceed 8.

#### OITC Rating

The Outdoor-Indoor Transmission Class (OITC) is calculated by subtracting the logarithmic summation of the TL values from the logarithmic summation of the A-weighted transportation noise spectrum stated in ASTM E1332.

## TEST REPORT FOR THERMA-TRU CORPORATION

Report No.: K7954.01-113-11-R2

Revision 2 Date: 04/12/22 Date: 03/19/20

### SECTION 9

#### SPECIMEN DESCRIPTION

	FRAME
SIZE	37-5/8" by 98"
THICKNESS	4-1/2"
CORNERS	Butted
FASTENERS	Screws
SEAL METHOD	N/A
MATERIAL	Wood
REINFORCEMENT	N/A
THERMAL BREAK MATERIAL	N/A
DAYLIGHT OPENING SIZE	N/A
SPECIMEN WEIGHT (lbs)	25

#### COMMENTS

The SMC skins with foam-fill leaf was 36" by 96" and 1-3/4" thick with a day light opening of 21-1/2" by 74-1/2" and weighed 95 lbs. Per the client's request, the contents of the door leaf are proprietary.

MEASURED OVERALL INSULATION GLASS UNIT THICKNESS	0.986"
SPACER TYPE	Aluminum

	EXTERIOR SHEET	GAP	INTERIOR SHEET
MEASURED THICKNESS	0.119"	0.746"	0.121"
MUNTIN PATTERN	N/A	N/A	N/A
MATERIAL	Tempered	Air*	Tempered
LAMINATE MATERIAL	N/A	N/A	N/A

GLAZING METHOD	Channel
GLAZING MATERIAL	Foam tape
GLAZING BEAD MATERIAL	N/A

\* - Stated per Client/Manufacturer, N/A-Not Applicable

#### COMMENTS

Whether the tested door system utilizes wood or composite stile edges, the ratings would remain unchanged.

## TEST REPORT FOR THERMA-TRU CORPORATION

Report No.: K7954.01-113-11-R2

Revision 2 Date: 04/12/22 Date: 03/19/20

	TYPE	QUANTITY	LOCATION
<b>WEATHERSTRIP</b>	Standard reach kerf mounted compression gasket	1 Row	Hinge jamb
	Long reach kerf mounted compression gasket	1 Row	Lock jamb and head
	Dual 3/8" Hollow bulb with four leaf kerf mounted sweep	1	Bottom rail
<b>HARDWARE</b>	Hinge	4	Hinge jamb
	Lock assembly set	1	Lock stile
	Dead bolt	1	Lock stile
	Strike plate	1	Lock jamb
	Adjustable aluminum threshold	1	Sill
<b>DRAINAGE</b>	Sloped sill	1	Sill

TOTAL WEIGHT (lbs)	AVERAGE WEIGHT (lbs/ft <sup>2</sup> )
120	4.69

Photographs are included in Section 11.

The client did not supply a report drawing of the test specimen.



## TEST REPORT FOR THERMA-TRU CORPORATION

Report No.: K7954.01-113-11-R2

Revision 2 Date: 04/12/22 Date: 03/19/20

### SECTION 10

#### TEST RESULTS

#### K7954.01A3 DATA

<b>SPECIMEN AREA</b>	2.38 m <sup>2</sup>	<b>RECEIVE TEMP.</b>	21.2 °C	<b>SOURCE TEMP</b>	21.2 °C
<b>TECHNICIAN</b>	Andrew M Jc	<b>RECEIVE HUMIDITY</b>	42%	<b>SOURCE HUMIDIT</b>	43%

FREQ (Hz)	BACKGROUND SPL (dB)	ABSORPTION (m <sup>2</sup> )	SOURCE SPL (dB)	RECEIVE SPL (dB)	SPECIMEN TL (dB)	95% CONFIDENCE LIMIT	NUMBER OF DEFICIENCIES
80	36.3	5.3	103	80	20	1.98	-
100	36.3	5.6	104	80	21	1.76	-
125	35.9	5.6	105	82	19	1.54	0
160	39.5	5.4	107	85	19	0.81	0
200	37.8	5.2	107	83	20	0.53	0
250	31.4	5.7	103	80	19	0.53	4
315	25.3	6.1	104	75	24	0.56	2
400	22.4	6.2	103	71	28	0.27	1
500	18.9	6.6	102	66	32	0.52	0
630	19.3	6.2	102	65	33	0.14	0
800	16.6	6.5	101	66	30	0.24	2
1000	12.2	6.8	102	69	28	0.20	5
1250	10.6	7.2	100	65	31	0.34	3
1600	8.6	7.7	99	64	30	0.15	4
2000	8.3	8.3	100	67	28	0.23	6
2500	9.2	9.4	101	59	36	0.18	0
3150	10.3	11.0	99	53	39	0.10	0
4000	11.9	13.6	97	55	34	0.21	0
5000	13.2	17.7	97	50	39	0.19	-
<b>STC RATING</b>	30 (Sound Transmission Class)						
<b>DEFICIENCIES</b>	27 (Sum of Deficiencies)						
<b>OITC RATING</b>	26 (Outdoor-Indoor Transmission Class)						


- Notes:**
- 1) Receive Room levels less than 5 dB above the Background levels are red.
  - 2) Specimen TL levels listed in red indicate the lower limit of the transmission loss.
  - 3) Specimen TL levels listed in green indicate that there has been a filler wall correction applied

## TEST REPORT FOR THERMA-TRU CORPORATION

Report No.: K7954.01-113-11-R2

Revision 2 Date: 04/12/22 Date: 03/19/20

### K7954.01A3 GRAPH



**TEST REPORT FOR THERMA-TRU CORPORATION**

Report No.: K7954.01-113-11-R2

Revision 2 Date: 04/12/22 Date: 03/19/20

**K7954.01A4 DATA**

<b>SPECIMEN AREA</b>	2.38 m <sup>2</sup>	<b>RECEIVE TEMP.</b>	21.2 °C	<b>SOURCE TEMP</b>	21.2 °C
<b>TECHNICIAN</b>	Andrew M Jc	<b>RECEIVE HUMIDITY</b>	42%	<b>SOURCE HUMIDIT</b>	43%

FREQ (Hz)	BACKGROUND SPL (dB)	ABSORPTION (m <sup>2</sup> )	SOURCE SPL (dB)	RECEIVE SPL (dB)	SPECIMEN TL (dB)	95% CONFIDENCE LIMIT	NUMBER OF DEFICIENCIES
80	37.0	5.2	104	81	20	2.09	-
100	34.9	5.6	105	79	22	2.02	-
125	36.2	6.0	105	82	19	1.62	0
160	40.2	5.3	107	84	19	0.78	0
200	38.2	5.0	107	83	20	0.48	0
250	31.4	5.7	103	81	18	0.53	5
315	25.1	6.0	104	75	25	0.75	1
400	22.4	6.2	103	71	28	0.28	1
500	18.8	6.4	102	66	32	0.57	0
630	19.1	6.3	102	65	33	0.18	0
800	17.2	6.6	101	66	31	0.21	1
1000	13.2	6.8	102	69	29	0.16	4
1250	10.0	7.3	100	65	31	0.33	3
1600	8.5	7.7	99	64	29	0.18	5
2000	8.2	8.2	100	67	28	0.21	6
2500	8.3	9.3	101	59	36	0.19	0
3150	9.2	11.0	99	53	39	0.13	0
4000	10.9	13.8	97	54	36	0.13	0
5000	12.0	17.6	97	50	39	0.18	-
<b>STC RATING</b>	30 (Sound Transmission Class)						
<b>DEFICIENCIES</b>	26 (Sum of Deficiencies)						
<b>OITC RATING</b>	25 (Outdoor-Indoor Transmission Class)						


- Notes:**
- 1) Receive Room levels less than 5 dB above the Background levels are red.
  - 2) Specimen TL levels listed in red indicate the lower limit of the transmission loss.
  - 3) Specimen TL levels listed in green indicate that there has been a filler wall correction applied

## TEST REPORT FOR THERMA-TRU CORPORATION

Report No.: K7954.01-113-11-R2

Revision 2 Date: 04/12/22 Date: 03/19/20

### K7954.01A4 GRAPH



## TEST REPORT FOR THERMA-TRU CORPORATION

Report No.: K7954.01-113-11-R2

Revision 2 Date: 04/12/22 Date: 03/19/20

### K7954.01B DATA

<b>SPECIMEN AREA</b>	2.38 m <sup>2</sup>	<b>RECEIVE TEMP.</b>	21.2 °C	<b>SOURCE TEMP</b>	21.1 °C
<b>TECHNICIAN</b>	Andrew M Jc	<b>RECEIVE HUMIDITY</b>	43%	<b>SOURCE HUMIDIT</b>	44%

FREQ (Hz)	BACKGROUND SPL (dB)	ABSORPTION (m <sup>2</sup> )	SOURCE SPL (dB)	RECEIVE SPL (dB)	SPECIMEN TL (dB)	95% CONFIDENCE LIMIT	NUMBER OF DEFICIENCIES
80	36.2	5.4	104	81	19	2.11	-
100	34.6	5.6	105	81	20	1.84	-
125	36.1	5.7	105	83	18	1.48	0
160	39.8	5.4	107	85	19	0.76	0
200	38.1	5.2	107	83	21	0.46	0
250	31.4	5.9	103	80	19	0.49	4
315	24.6	6.1	104	75	24	0.53	2
400	22.0	6.2	103	71	28	0.37	1
500	18.6	6.5	102	66	32	0.57	0
630	18.7	6.3	102	66	32	0.16	0
800	17.2	6.5	101	65	31	0.27	1
1000	13.0	6.8	102	69	29	0.15	4
1250	10.5	7.3	100	64	31	0.31	3
1600	8.5	7.7	99	65	29	0.19	5
2000	8.5	8.4	100	65	29	0.25	5
2500	8.9	9.4	101	58	37	0.17	0
3150	9.7	11.1	99	53	40	0.13	0
4000	11.4	14.1	97	54	35	0.15	0
5000	12.5	18.2	97	49	39	0.22	-
<b>STC RATING</b>	30 (Sound Transmission Class)						
<b>DEFICIENCIES</b>	25 (Sum of Deficiencies)						
<b>OITC RATING</b>	25 (Outdoor-Indoor Transmission Class)						


- Notes:**
- 1) Receive Room levels less than 5 dB above the Background levels are red.
  - 2) Specimen TL levels listed in red indicate the lower limit of the transmission loss.
  - 3) Specimen TL levels listed in green indicate that there has been a filler wall correction applied

## TEST REPORT FOR THERMA-TRU CORPORATION

Report No.: K7954.01-113-11-R2

Revision 2 Date: 04/12/22 Date: 03/19/20

### K7954.01B GRAPH



**TEST REPORT FOR THERMA-TRU CORPORATION**

Report No.: K7954.01-113-11-R2

Revision 2 Date: 04/12/22 Date: 03/19/20

**K7954.01B1 DATA**

<b>SPECIMEN AREA</b>	2.38 m <sup>2</sup>	<b>RECEIVE TEMP.</b>	21.2 °C	<b>SOURCE TEMP</b>	21.1 °C
<b>TECHNICIAN</b>	Andrew M Jc	<b>RECEIVE HUMIDITY</b>	43%	<b>SOURCE HUMIDIT</b>	44%

FREQ (Hz)	BACKGROUND SPL (dB)	ABSORPTION (m <sup>2</sup> )	SOURCE SPL (dB)	RECEIVE SPL (dB)	SPECIMEN TL (dB)	95% CONFIDENCE LIMIT	NUMBER OF DEFICIENCIES
80	36.2	5.2	103	80	20	1.98	-
100	34.6	5.5	105	80	21	1.94	-
125	36.1	6.2	105	82	19	1.55	0
160	39.8	5.4	107	85	19	0.65	0
200	38.1	5.1	107	83	20	0.53	0
250	31.4	5.8	103	81	18	0.54	5
315	24.6	6.1	104	75	25	0.59	1
400	22.0	6.3	103	71	28	0.29	1
500	18.6	6.5	102	66	32	0.54	0
630	18.7	6.3	102	65	33	0.19	0
800	17.2	6.5	101	65	31	0.24	1
1000	13.0	6.7	102	69	29	0.20	4
1250	10.5	7.3	100	64	31	0.34	3
1600	8.5	7.7	99	65	29	0.18	5
2000	8.5	8.4	100	65	30	0.22	4
2500	8.9	9.4	101	58	37	0.16	0
3150	9.7	11.1	99	52	40	0.14	0
4000	11.4	14.0	97	52	37	0.12	0
5000	12.5	18.1	97	49	39	0.22	-
<b>STC RATING</b>	30 (Sound Transmission Class)						
<b>DEFICIENCIES</b>	24 (Sum of Deficiencies)						
<b>OITC RATING</b>	25 (Outdoor-Indoor Transmission Class)						


- Notes:**
- 1) Receive Room levels less than 5 dB above the Background levels are red.
  - 2) Specimen TL levels listed in red indicate the lower limit of the transmission loss.
  - 3) Specimen TL levels listed in green indicate that there has been a filler wall correction applied

## TEST REPORT FOR THERMA-TRU CORPORATION

Report No.: K7954.01-113-11-R2

Revision 2 Date: 04/12/22 Date: 03/19/20

### K7954.01B1 GRAPH





**TEST REPORT FOR THERMA-TRU CORPORATION**

Report No.: K7954.01-113-11-R2

Revision 2 Date: 04/12/22 Date: 03/19/20

**K7954.01C DATA**

<b>SPECIMEN AREA</b>	2.38 m <sup>2</sup>	<b>RECEIVE TEMP.</b>	21.2 °C	<b>SOURCE TEMP</b>	21.2 °C
<b>TECHNICIAN</b>	Andrew M Jc	<b>RECEIVE HUMIDITY</b>	43%	<b>SOURCE HUMIDIT</b>	43%

FREQ (Hz)	BACKGROUND SPL (dB)	ABSORPTION (m <sup>2</sup> )	SOURCE SPL (dB)	RECEIVE SPL (dB)	SPECIMEN TL (dB)	95% CONFIDENCE LIMIT	NUMBER OF DEFICIENCIES
80	33.2	4.8	103	79	21	1.85	-
100	32.3	5.8	105	80	21	2.09	-
125	33.7	6.3	105	83	18	1.60	0
160	39.7	5.7	107	85	18	0.76	0
200	38.1	5.1	107	83	21	0.57	0
250	30.8	5.9	102	80	18	0.56	5
315	24.1	6.0	104	75	25	0.58	1
400	21.2	6.2	103	71	28	0.32	1
500	17.9	6.6	102	66	32	0.58	0
630	18.3	6.3	102	65	33	0.15	0
800	17.1	6.6	101	66	30	0.24	2
1000	11.9	6.7	102	69	29	0.20	4
1250	10.5	7.2	100	65	31	0.34	3
1600	8.7	7.7	99	65	28	0.18	6
2000	8.5	8.3	100	66	29	0.21	5
2500	11.0	9.5	101	59	36	0.17	0
3150	9.7	11.0	99	53	40	0.13	0
4000	11.7	14.2	97	55	35	0.16	0
5000	13.0	18.3	97	50	38	0.23	-
<b>STC RATING</b>	30 (Sound Transmission Class)						
<b>DEFICIENCIES</b>	27 (Sum of Deficiencies)						
<b>OITC RATING</b>	25 (Outdoor-Indoor Transmission Class)						


- Notes:**
- 1) Receive Room levels less than 5 dB above the Background levels are red.
  - 2) Specimen TL levels listed in red indicate the lower limit of the transmission loss.
  - 3) Specimen TL levels listed in green indicate that there has been a filler wall correction applied

## TEST REPORT FOR THERMA-TRU CORPORATION

Report No.: K7954.01-113-11-R2

Revision 2 Date: 04/12/22 Date: 03/19/20

### K7954.01C GRAPH



## TEST REPORT FOR THERMA-TRU CORPORATION

Report No.: K7954.01-113-11-R2

Revision 2 Date: 04/12/22 Date: 03/19/20

### K7954.01C1 DATA

<b>SPECIMEN AREA</b>	2.38 m <sup>2</sup>	<b>RECEIVE TEMP.</b>	21.2 °C	<b>SOURCE TEMP</b>	21.2 °C
<b>TECHNICIAN</b>	Andrew M Jc	<b>RECEIVE HUMIDITY</b>	43%	<b>SOURCE HUMIDIT</b>	43%

FREQ (Hz)	BACKGROUND SPL (dB)	ABSORPTION (m <sup>2</sup> )	SOURCE SPL (dB)	RECEIVE SPL (dB)	SPECIMEN TL (dB)	95% CONFIDENCE LIMIT	NUMBER OF DEFICIENCIES
80	33.2	5.1	104	81	19	2.23	-
100	32.3	5.2	105	80	21	2.00	-
125	33.7	5.9	105	82	18	1.57	0
160	39.7	5.4	107	85	18	0.78	0
200	38.1	5.2	107	83	21	0.51	0
250	30.8	5.8	102	81	18	0.55	5
315	24.1	6.0	103	75	25	0.59	1
400	21.2	6.3	103	71	28	0.31	1
500	17.9	6.6	102	66	32	0.59	0
630	18.3	6.2	102	65	33	0.15	0
800	17.1	6.6	101	66	31	0.21	1
1000	11.9	6.8	102	69	29	0.16	4
1250	10.5	7.2	100	65	31	0.31	3
1600	8.7	7.6	99	65	28	0.17	6
2000	8.5	8.3	100	66	29	0.22	5
2500	11.0	9.4	101	59	37	0.18	0
3150	9.7	11.1	99	53	40	0.14	0
4000	11.7	14.1	97	53	36	0.16	0
5000	13.0	18.3	97	50	39	0.23	-
<b>STC RATING</b>	30 (Sound Transmission Class)						
<b>DEFICIENCIES</b>	26 (Sum of Deficiencies)						
<b>OITC RATING</b>	25 (Outdoor-Indoor Transmission Class)						


- Notes:**
- 1) Receive Room levels less than 5 dB above the Background levels are red.
  - 2) Specimen TL levels listed in red indicate the lower limit of the transmission loss.
  - 3) Specimen TL levels listed in green indicate that there has been a filler wall correction applied

## TEST REPORT FOR THERMA-TRU CORPORATION

Report No.: K7954.01-113-11-R2

Revision 2 Date: 04/12/22 Date: 03/19/20

### K7954.01C1 GRAPH



## TEST REPORT FOR THERMA-TRU CORPORATION

Report No.: K7954.01-113-11-R2

Revision 2 Date: 04/12/22 Date: 03/19/20

### SECTION 11

#### PHOTOGRAPHS



**Photo No. 1**  
**Receive Room View of Installed Test Specimen**



**Photo No. 2**  
**Source Room View of Installed Test Specimen**

## TEST REPORT FOR THERMA-TRU CORPORATION

Report No.: K7954.01-113-11-R2

Revision 2 Date: 04/12/22 Date: 03/19/20

### SECTION 12

#### REVISION LOG

REVISION #	DATE	PAGES	REVISION
0	03/19/20	N/A	Original Report Issue
1	05/08/20	1, 3, 7	Added flush glazed to Series/Model, and changed comments to state SMC skins
2	04/12/22	4, 7	Added Comments